





POZ. A/A/2/00 60x90
Skala 1:25 Szt. 1




POZ. A/B/00 50x90
Skala 1:25 Szt. 1



ZESTAWIENIE STALI ZBROJENIOWEJ STAL A-III/N				
Poz.	Szt.	d	n Razem (n)	Ciezar (kg)
1	6	25	7.40	44.40
2	4	25	7.36	29.44
3	12	20	2.48	29.76
4	6	12	5.32	23.12
5	8	8	2.26	194.36
6	4	8	2.44	104.92
7	6	12	7.10	42.60
8	24	8	0.68	16.32
9	20	16	1.95	39.00
10	4	20	3.97	15.88
11	8	8	1.20	9.60
12	3	16	2.75	8.25
13	9	8	2.61	23.49
14	20	16	1.95	39.00
15	8	8	1.20	9.60
16	6	25	7.45	44.70
17	6	25	7.29	42.74
18	6	20	3.23	19.38
19	6	20	3.96	23.76
20	12	20	2.54	30.48
21	6	12	3.94	23.64
22	6	25	4.69	28.14
23	4	25	2.50	10.00
24	6	12	5.18	23.08
25	14	8	2.18	318.28
26	73	8	2.32	169.36
27	6	20	6.81	40.86
28	6	20	5.51	33.06
29	6	12	7.28	43.68
30	4	8	0.58	25.32
31	12	20	3.15	37.80
32	6	12	4.11	24.66
33	76	8	2.26	171.76
34	38	8	2.44	92.72
35	16	12	6.81	108.96
36	72	8	0.68	40.36
37	42	8	4.28	179.76
38	3	16	6.81	20.43
39	32	8	0.32	10.24
40	3	16	2.75	8.25
41	23	8	2.63	60.49
42	4	8	1.20	4.80
43	10	16	1.95	39.00
44	8	20	3.97	31.76

ZEST. ZE WZGLĘDÓW NA ŚREDNIEJ				
d(m)	Razem (n)	kg/n	Ciezar (kg)	
8	1440	0.395	568.80	
12	307.74	0.880	270.77	
16	134.43	1.580	212.39	
20	262.74	2.470	648.96	
25	200.42	3.850	771.61	



WYKRYTIE STALOWYCH I PROFILI GŁĘBOKI PODŁOGI NA STANIE ZWYKŁYCH				
Poz.	Szt.	d	n Razem (n)	Ciezar (kg)
1	6	25	7.40	44.40
2	4	25	7.36	29.44
3	12	20	2.48	29.76
4	6	12	5.32	23.12
5	8	8	2.26	194.36
6	4	8	2.44	104.92
7	6	12	7.10	42.60
8	24	8	0.68	16.32
9	20	16	1.95	39.00
10	4	20	3.97	15.88
11	8	8	1.20	9.60
12	3	16	2.75	8.25
13	9	8	2.61	23.49
14	20	16	1.95	39.00
15	8	8	1.20	9.60
16	6	25	7.45	44.70
17	6	25	7.29	42.74
18	6	20	3.23	19.38
19	6	20	3.96	23.76
20	12	20	2.54	30.48
21	6	12	3.94	23.64
22	6	25	4.69	28.14
23	4	25	2.50	10.00
24	6	12	5.18	23.08
25	14	8	2.18	318.28
26	73	8	2.32	169.36
27	6	20	6.81	40.86
28	6	20	5.51	33.06
29	6	12	7.28	43.68
30	4	8	0.58	25.32
31	12	20	3.15	37.80
32	6	12	4.11	24.66
33	76	8	2.26	171.76
34	38	8	2.44	92.72
35	16	12	6.81	108.96
36	72	8	0.68	40.36
37	42	8	4.28	179.76
38	3	16	6.81	20.43
39	32	8	0.32	10.24
40	3	16	2.75	8.25
41	23	8	2.63	60.49
42	4	8	1.20	4.80
43	10	16	1.95	39.00
44	8	20	3.97	31.76

WYKRYTIE STALOWYCH I PROFILI GŁĘBOKI PODŁOGI NA STANIE ZWYKŁYCH				
Poz.	Szt.	d	n Razem (n)	Ciezar (kg)
1	6	25	7.40	44.40
2	4	25	7.36	29.44
3	12	20	2.48	29.76
4	6	12	5.32	23.12
5	8	8	2.26	194.36
6	4	8	2.44	104.92
7	6	12	7.10	42.60
8	24	8	0.68	16.32
9	20	16	1.95	39.00
10	4	20	3.97	15.88
11	8	8	1.20	9.60
12	3	16	2.75	8.25
13	9	8	2.61	23.49
14	20	16	1.95	39.00
15	8	8	1.20	9.60
16	6	25	7.45	44.70
17	6	25	7.29	42.74
18	6	20	3.23	19.38
19	6	20	3.96	23.76
20	12	20	2.54	30.48
21	6	12	3.94	23.64
22	6	25	4.69	28.14
23	4	25	2.50	10.00
24	6	12	5.18	23.08
25	14	8	2.18	318.28
26	73	8	2.32	169.36
27	6	20	6.81	40.86
28	6	20	5.51	33.06
29	6	12	7.28	43.68
30	4	8	0.58	25.32
31	12	20	3.15	37.80
32	6	12	4.11	24.66
33	76	8	2.26	171.76
34	38	8	2.44	92.72
35	16	12	6.81	108.96
36	72	8	0.68	40.36
37	42	8	4.28	179.76
38	3	16	6.81	20.43
39	32	8	0.32	10.24
40	3	16	2.75	8.25
41	23	8	2.63	60.49
42	4	8	1.20	4.80
43	10	16	1.95	39.00
44	8	20	3.97	31.76